



Válvula diafragma cuerpo de plástico serie SLP/ESP

| Port Size | Orifice (mm) | CV Value | Min. Pressure | Pressure Difference (Bar) | | | Max. Temperature (°C) | Power | | Model 220VAC 50/60Hz | |
|---------------|--------------|----------|---------------|-----------------------------|--------------------------|-------------------|-----------------------|--------|--------|----------------------|-----------------|
| | | | | Max. Working Pressure | | | | AC 220 | DC 24V | Brass | Stainless Steel |
| | | | | Air, Gas | Water, Hot Water, Liquid | Light Oil ≤20CSTT | | | | | |
| 1-1/2" | 40 | 30 | 0.5 | 8 | 8 | 7 | 80 | 33 | 32 | SLP-40E2H | SLP-40E2S1H |
| | 40 | 30 | 0.5 | 8 | 8 | 8 | 120 | 33 | 32 | SLP-40EE2H | SLP-40EE2S1H |
| | 40 | 30 | 0.5 | 8 | 8 | 7 | 120 | 33 | 32 | SLP-40VE2H | SLP-40VE2S1H |
| 2" | 50 | 48 | 0.5 | 8 | 8 | 7 | 80 | 33 | 32 | SLP-50E2H | SLP-50E2S1H |
| | 50 | 48 | 0.5 | 8 | 8 | 8 | 120 | 33 | 32 | SLP-50EE2H | SLP-50EE2S1H |
| | 50 | 48 | 0.5 | 8 | 8 | 7 | 120 | 33 | 32 | SLP-50VE2H | SLP-50VE2S1H |
| Flange 4 port | 25 | 12 | 0.5 | 8 | 8 | 7 | 80 | 33 | 32 | --- | SLPFE2-25LS1H |
| | 25 | 12 | 0.5 | 8 | 8 | 8 | 120 | 33 | 32 | --- | SLPFEE2-25LS1H |
| | 25 | 12 | 0.5 | 8 | 8 | 7 | 120 | 33 | 32 | --- | SLPFVE2-25LS1H |
| Flange 4 port | 35 | 22 | 0.5 | 8 | 8 | 7 | 80 | 33 | 32 | --- | SLPFE2-35LS1H |
| | 35 | 22 | 0.5 | 8 | 8 | 8 | 120 | 33 | 32 | --- | SLPFEE2-35LS1H |
| | 35 | 22 | 0.5 | 8 | 8 | 7 | 120 | 33 | 32 | --- | SLPFVE2-35LS1H |
| Flange 4 port | 40 | 30 | 0.5 | 8 | 8 | 7 | 80 | 33 | 32 | --- | SLPFE2-40LS1H |
| | 40 | 30 | 0.5 | 8 | 8 | 8 | 120 | 33 | 32 | --- | SLPFEE2-40LS1H |
| | 40 | 30 | 0.5 | 8 | 8 | 7 | 120 | 33 | 32 | --- | SLPFVE2-40LS1H |
| Flange 4 port | 50 | 48 | 0.5 | 8 | 8 | 7 | 80 | 33 | 32 | --- | SLPFE2-50LS1H |
| | 50 | 48 | 0.5 | 8 | 8 | 8 | 120 | 33 | 32 | --- | SLPFEE2-50LS1H |
| | 50 | 48 | 0.5 | 8 | 8 | 7 | 120 | 33 | 32 | --- | SLPFVE2-50LS1H |

Válvula diafragma cuerpo de plástico serie ESP

How to Order?

| | | | | |
|------------|---|---|----|---|
| ESP | - | 10 | -- | E2 |
| ESP Series | | Port size 10: 3/8" 15: 1/2" 20: 3/4" 25: 1" 35: 1-1/4" 40: 1-1/2" | | Voltage E1: AC110V E8: DC110V E2: AC220V E9: DC48V E3: AC380V E10: DC36V E4: DC24V E5: DC12V E6: AC36V E7: AC24V |



ESP-10

Order example:

* ESP series, 2 position, 2 port, AC110V, 3/8" port size, Normal Close, Model: ESP-10E1

Specifications

| Model | ESP-10 | ESP-15 | ESP-20 | ESP-25 | ESP-35 | ESP-40 |
|-------------------------|-------------------------|--------|--------|--------|--------|--------|
| Working Medium | Air, Gas, Water, Liquid | | | | | |
| Working Temperature(°C) | 0-65 | | | | | |
| Working Style | Diaphragm | | | | | |
| Orifice(mm) | 15 | 15 | 25 | 25 | 40 | 40 |
| Joint Size | 3/8" | 1/2" | 3/4" | 1" | 1-1/4" | 1-1/2" |
| CV Valve | | | | | | |
| Working Pressure(Bar) | 0.5-7 | | | | | |
| Max. Pressure(Bar) | 9 | | | | | |
| Valve Body | Reinforce Nylon | | | | | |